



PrimaJet is designed to meet the demands of ink jet printing for publications of up to four colours. Ideal for books containing detailed illustrations, PrimaJet is available from 40 to 50 g/m².

Given the variety of digital press' available in the market today, we strongly recommend that you contact us prior to ordering.

FSC or PEFC on request

Specifications					
Characteristics	Unit	Standard			
Code			PNJ40WST	PNJ45WST	PNJ50WST
Grammage	g/m ²	ISO 536	40 g/m ²	45 g/m ²	50 g/m ²
Grammage (USA)	lbs		27.0	30.4	33.8
Thickness	µm	ISO 534	47	52	57
Bulk	cm ³ /g	-	1.17	1.15	1.14
Whiteness	%	ISO 2470	87	87	87
Opacity	%	ISO 2471	82.5	85	86
Absolute humidity	%	NF Q03-003	5.5	5.5	5.5
Ability ink jet	-	PDL		YES	
Permanent paper	-	ISO 9706		YES	
Optical brightner	-	-		NO	

Paper tolerances	
Grammage: nominal value + / - 1 g/m ²	ISO opacity minimum: nominal value 1 point
Thickness: + / - 2 µm	Absolute humidity: + / - 0.5%
ISO whiteness minimum: nominal value 1 point	

Minimum making: Quantity required by the mill will be dependent on both the production schedules and the possibilities at the time of the order for a combination of widths to cover the machine deckle. Please contact your sales representative for more details.

Measurements made on Jumbo rolls according to the Standards and Norms in place at that time.

Validated: 09/01/2014

Qualified by Hervé Brunet-Jailly – Technical Support Manager